

Olympus™ Flat Top



FLAT TOP: **One-piece upholstered top, square corners, 3 layer foam**

Foam	3/4" firm bottom, 1- 3/4" medium middle, urethane polymer
Polyester batting	1/2" fluffy polyester Dacron top layer
Upholstered top & frame	30" width x 73" length x 6" thickness
Subframe	None
Leg Frame	20.5" width x 56.5 length x 5" thickness

TOP OPTIONS:

Footrests and face supports No extra holes needed

VINYL CHOICES:

Ultra Soft Touch - standard Lightly textured, Super Soft Urethane vinyl, fabric backed, environmentally friendly

BASE:

Outside leg spacing	25" width x 56" length
Inside leg spacing	20" width x 51" length
Base materials	Maple legs with 3/4" plywood
Parallel Lift Bars	Two powder-coated carbon steel lift bars connect to motor
Adjustable leg extension	1/4" leg bolts w/ 2 knobs, 11 holes, felt backed, 2 rubber bumpers per leg
Height range	19" to 41" Double adjustable: 10" manual (ext. legs) & 12" electric lift
Leg Recess	4" Recess on sides, 12" recess from head section

ELECTRIC LIFT:

Power requirements	110 volt 10 amp breaker is sufficient
Floating foot pedal	One up and one down pedal
Lift mechanism	1-24 volt motor powered through a 110 volt, 5 amp transformer
Motor-Linak LA28	24 VDC permanent magnet motor, UL listed
240-volt model (international)	Available at no extra charge

BASE OPTIONS:





Extra-low-range legs 14" to 24" (electric lift only, short non-adjusting legs replace ext. legs)

GUARANTEES:

Structure and foam	5 yrs.
Vinyl	Guaranteed to arrive in good condition
Motor/actuator & transformer	1 yr.

WEIGHTS:

Weight:	79 lbs.
Shipping weight:	120 lbs.



Rev 7/1/07



PO Box 1304 Dimmocks Mill Rd
International: 919.732.6968

Toll Free: 800.678.6824

Fax: 919.732.1173