



Contour[®]

Technical Specifications



Motor -	1/17 horsepower
Output Speed -	10-60 cycles per second
Power Source -	110v or 220v (other voltages available upon request)
Speed Control -	Solid State Electronic
Current Leakage -	under 75 MicroAmps
Power Cord -	10' hospital grade
Drive Cable -	5'
Housing Material -	ABS Cycolac
Configurations -	Caster-stand mounted, table-top mounted, or wall-mounted (hardware sold seperately)
Unit Dimensions -	7 1/2" H x 13" W x 14" D
Assembled Dimensions -	44" H x 21" W x 21" D
Unit Weight -	15.75 Lbs.
Assembled Unit Weight -	25 Lbs.
Shipping Dimensions -	22" x 21" x 17 3/8"
Shipping Weight -	36 Lbs. (varies based on applicator package)
Applicator Packages -	SPA-PKG recommended
Timer -	Yes
Applicator Storage -	Yes - tray



GENERAL PHYSIOTHERAPY, INC.
 13222 LAKEFRONT DRIVE - EARTH CITY (ST. LOUIS), MISSOURI 63045-1504 - USA
 PHONE: (314) 291-1442 TOLL FREE: (800) 237-1832 FAX: (314) 291-1485
www.g5.com

